

TS-2000 Series Spartan Two-Way Business Radios

TS-2116 2 Watt VHF (136-174 MHz) TS-2416 2 Watt UHF (400-470 MHz)







The SPARTAN TS-2000 Series are durable, lightweight, and easy to use. Delivers clear, reliable communications for hotels, restaurants, shopping mall, super market, property management and other industrial, commercial needs.

Preprogrammed to operate with other Jobsite Business Radios or fully programmable to existing simplex channels, repeater systems or independent FCC licensed frequencies.



- · 16 Channels
- · Optional Voice Annunciation
- · 2 Watt Power Output
- 12.5/25 kHz Channel Spacing
- · CTCSS/DCS
- · 700 mw Audio Output
- · Time-Out Timer (TOT)
- · Power Save Mode
- · VOX
- · One Year Warranty





NOTE: Some features indicated by specifications listed are prohibited by FCC rule and are not available on models sold in the U.S. or its territories.

Specifications

General

TS-2116 136-174 MHz
TS-2416 400-470 MHz
Operating Voltage 3.8V DC

Operating Temperature -13° to 131° F (-25° to 55° C)

Frequency Stability ± 2.5 PPM

Dimensions (H/W/D) 4.1 x 2.1 x 1.1 (105 x 54 x 30 mm)

Channel Spacing 12.5 kHz per channel

PLL Stepping 2.5/6.25 kHz

Weight with Li-Ion Battery 5.9 oz. (170 g.) w/battery

Battery Life (hours) 14 h

Battery Drain mAh

Tx 1200, Rx 300, Stby 60

Battery Capacity 2000 mAh Li-Ion

Charge Time Estimate 2-3 hours

*90/5/5 duty cycle with battery save

 Approvals
 FCC
 Industry Canada

 TS-2116
 P6N-TH288V
 / 9680A-TS-2116

 TS-2416
 P6N-TH288U
 / 9680A-TS-2416





Transmitter

Output Power 2 Watt, UHF/VHF Spurious and Harmonic -36dB (1 GHz), -30dB (1 GHz)

FM Hum and Noise -40dB (12.5 kHz), -45dB (25 kHz)

Audio Distortion <5%

Adjacent Channel Power -70dB, -60dB

TS-2000 Series

Spartan Two-Way Business Radios

Standard Package

Radio, 2000 mAh Li-Ion battery, rapid rate desktop charger, antenna, belt clip and user manual.

Accessories

- · Standard Speaker Microphone
- · Heavy Duty Speaker Microphone
- Earhook Speaker with Lapel Mic
- Discreet Earbud with Lapel Mic
- Nylon Carrying Case
- Single Slot Vehicular Charger
- Six Unit Gang Charger
- Programming Software and Cable

Contact Information

Receiver

Sensitivity .18uV / .20uV
Selectivity 65dB / 55dB
FM Hum and Noise 40dB
Audio Output Power 700 mW

Audio Distortion <5% at rated output

Intermodulation Reject Ratio 55dB



TecNet International, Inc.

11535 W. 83rd Terrace, Lenexa, KS 66214

Tel: 800-456-2071 Toll Free U.S.

Tel: 913-859-9515
Fax: 913-859-9550
Web: www.tecnetusa.com
E-mail: tecnet@tecnetusa.com