

TS-3000 Series

Spartan Two-Way Business Radio

TS-3116 5/1W VHF (136-174 MHz) TS-3416 4/1W UHF (400-470 MHz)







The SPARTAN TS-3000 Series are durable, lightweight, and easy to use. Delivers clear, reliable communications for hotels, restaurants, retail stores, shopping centers, property management and other industrial, commercial needs.

Preprogrammed to operate with other Jobsite Business Radios or fully programmable to existing simplex channels, repeater systems or independent FCC licensed frequencies.



- 16 Channels
- Optional Voice Annunciation
- 5/1 VHF, 4/1 UHF Watt Power Output
- 12.5/25 kHz Channel Spacing
- CTCSS/DCS
- 700 mw Audio Output
- Time-Out Timer (TOT)
- Power Save Mode
- VOX
- One Year Warranty





NOTE: Some features indicated by specifications listed are prohibited by FCC rule and are not available on models sold in the U.S. or its territories.

Specifications

General

TS-2116 136-174 MHz
TS-2416 400-470 MHz
Operating Voltage 7.5V DC

Operating Temperature -13° to 131° F (-25° to 55° C)

Frequency Stability ± 2.5 PPM

Dimensions (H/W/D) 4.6 x 2.2 x 1.3" (116 x 56 x 34 mm)

Channel Spacing 12.5 kHz per channel

PLL Stepping 2.5/6.25 kHz

Weight with Li-Ion Battery 7.2 oz. (203 g.) w/battery

Battery Life (hours) 14 h

Battery Drain mAh Tx 1200, Rx 300, Stby 60

Battery Capacity 1500 mAh Li-Ion

Charge Time Estimate 2-3 hours

*90/5/5 duty cycle with battery save

Approvals FCC Industry Canada

TS-3116 P6N-TH368V Pending TS-3416 P6N-TH368U Pending







Manufactured to ISO-9002:2000 quality standard.

Transmitter

Output Power Spurious and Harmonic FM Hum and Noise Audio Distortion 5/1 VHF, 4/1 UHF Watt

-36dBm (1 GHz), -30dBm (1 GHz) -40dB (12.5 kHz), -45dB (25 kHz)

<5%

Adjacent Channel Power -70dB/-60dB

TS-3000 Series

Spartan Two-Way Business Radio

Standard Package

Radio, 1500 mAh Li-Ion battery, rapid rate desktop charger, antenna, belt clip and user manual.

Accessories

- · Standard Speaker Microphone
- Heavy Duty Speaker Microphone
- · Earhook Speaker with Lapel Mic
- Discreet Earbud with Lapel Mic
- Nylon Carrying Case
- Leather Carrying Case with Belt Loop Swivel
- Single Slot Vehicular Charger
- · Six Unit Gang Charger
- Programming Software and Cable (USB)

Contact Information

Receiver

Sensitivity .25uV / .25uV / .25uV Selectivity 70dB / 60dB FM Hum and Noise 40dB Audio Output Power 700 mW

Audio Distortion 700 mw
45% at rated output

Intermodulation Reject Ratio 65dB



TecNet International, Inc.

11535 W. 83rd Terrace, Lenexa, KS 66214

Tel: 800-456-2071 Toll Free U.S.

Tel: 913-859-9515
Fax: 913-859-9550
Web: www.tecnetusa.com
E-mail: tecnet@tecnetusa.com